




Liquidtight Flexible Metal Conduit Fittings



Steel/malleable iron or aluminum tapered hub threads. With safe-edge ground through 4" cone and double bevel seating ring (through 2").



Malleable iron, tapered hub threads. With safe-edge ground cone and double bevel sealing ring (through 2").



52° and 53° Series Liquidtight Straight Connectors*



CAT. NO.		CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED STEEL	NON-INSULATED STEEL		A	B	C
5229†	—	¼"	27/32	1 3/8	15/32
5330†	—	5/16"	63/64	1 3/8	15/32
5331†**	5231†	3/8"	1 5/32	1 1/2	9/16
5332†	5232†	½"	1 1/8	1 1/16	9/16
5333†	5233†	¾"	1 21/32	1 5/8	9/16
5334†	5234†	1"	1 7/8	2 1/16	3/4
5335†	5235†	1 1/4"	2 29/32	2 1/2	13/16
5336	5236	1 ½"	2 23/32	2 1/16	13/16
5337	5237	2"	3 1/4	3 1/16	7/8
5338	5238	2 ½"	3 3/4	4 1/8	1
5339	5239	3"	4 1/2	4 1/4	1
5340	5240	4"	5 1/2	4 1/2	1 1/8
5385†	5285	5"	8 3/4	7	1 1/8
5386†	—	6"	8 3/4	8 1/2	2

52° and 53° Series Liquidtight 45° Angle Connectors*

CAT. NO.		CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED	NON-INSULATED		A	B	C
5341†**	5241†	3/8"	1 1/32	1 1/16	9/16
5342†	5242†	½"	1 3/8	1 1/8	9/16
5343†	5243†	¾"	1 21/32	2 1/8	9/16
5344†	5244†	1"	1 7/8	2 1/4	3/4
5345†	5245†	1 3/8"	2 29/32	2 3/4	13/16
5346	5246	1 ½"	2 23/32	3 3/8	13/16
5347	5247	2"	3 1/4	3 3/8	7/8
5348	5248	2 ½"	3 3/4	4 1/4	1
5349	5249	3"	4 1/2	4 1/4	1
5350	5250	4"	5 1/2	4 5/8	1 1/8

52° and 53° Series Liquidtight 90° Angle Connectors



CAT. NO.		HUB SIZE	CONDUIT SIZE	DIMENSIONS (IN.)		
INSULATED	NON-INSULATED			A	B	C
5351	5251	½"	3/8"	1 1/32	1 1/8	9/16
5352	5252	½"	½"	1 3/8	1 1/16	9/16
5353	5253	¾"	3/8"	1 21/32	1 3/4	9/16
5354	5254	1"	1"	1 7/8	2 1/8	3/4
5355	5255	1 ¼"	1 ¼"	2 29/32	2 3/4	13/16
5356	5256	1 ½"	1 ½"	2 23/32	2 1/16	13/16
5357	5257	2"	2"	3 1/4	3 1/16	7/8
5358	5258	2 ½"	2 ½"	3 3/4	8 1/8	1
5359	5259	3"	3"	4 1/2	10 1/4	1
5360	5260	4"	4"	5 1/2	12 1/8	1 1/8

* Suitable for hazardous locations use in Class I, Div. 2; Class II, Div. 1 and 2; Class III, Div. 1 and 2, where general purpose equipment is specifically permitted per NEC Section 500-2(a).

** 3/8" Conduit Fitting has 1/2" hub.

† UL Listed as grounding means under NEC 351-7.

‡ Not UL Listed.

Blue is a trademark color of Thomas & Betts.

Note: UL Listed liquidtight; and CSA Certified watertight. Available with DURA-PLATE™ Finish. UL File No. E-23018 CSA File No. 2884

For wire mesh grips refer to page A-114.